

## IV-106 COD DIGESTION SYSTEM


DIGITAL COD DIGESTER is suitable for COD method for monitoring wastewater influent and effluent, industrial process water, and more. This instrument is used by Pollution control labs.

### PRODUCT FEATURES

- Outer cabinet is made of mild steel duly powder coated.
- Double wall construction with insulation for minimum heat losses increases the efficiency of the system.
- Aluminum Block with holes (Dimension 38 mm Diameter x 76 mm Depth) is used to hold 15 Nos COD tubes.
- Aluminum Block is heated to maintain temperature up to 180° C
- Solid state Digital Temperature Controller, appropriate heater & insulation selection assure uniformity in all the samples.
- Selectable timer up to 120 min/h alarm is provided to set the digestion period (Refluxing).
- After digestion, analyze the sample with titrimetric method. (without chemicals and accessories for Titration)
- Supplied with 15 sets of Glassware (15 Nos. COD Tubes & 15 Nos. Air Condensers)



### Technical specification

Image	
Temperature Range	Above ambient to 180° C or higher
Temperature Resolution	0.1° C
Display	LED display
Control	Digital Electronic Temperature Controller
Heater Rating	750 Watts
Sensor	PT-100
Timer	Selectable 15, 30, 45, 60, 90 or 120 minutes with alarm
Hole Size	38mm Diameter x 76mm Depth
Glass Tube	36mm diameter, 15 no (3 x 5 rows)
Sample Volume	20 ml Each